

- > Up to 24 PPM
- > Black & White MFP
- > Small/Med. Workgroup
- > Copy, Print, Scan, Fax
- > Secure MFP
- > Eco Friendly





- > Black & White MFP
- > Up to 24 PPM
- > Small/Med Workgroup
- > Copy, Print, Scan, Fax
- > Eco Friendly

Special Features

- Interrupt
- Energy Saver
- AMS/APS
- Auto Job Start
- Auto Sort Mode
- Electronic Sort
- ID Card Copy
- Coin Controller Operation
- Access Code
- Department Code
- Magazine Sort
- 2-in-1, 4-in-1

General Specification

Type	Desktop
Copying/Printing Process	Indirect electrostatic photographic method
Copying Resolution	600 dpi / 256 Gradation
Scanning Resolution	600 dpi
Printing Resolution	2400 dpi x 600 dpi (with smoothing)
Copying Speed	19/22/24ppm
Std Copier Memory	112 MB
Max Copier Memory	112 MB
First Copy Out Time:	7.5 sec.
Warm-Up Time:	25 sec.
Multiple Copying:	Up to 999
Acceptable Paper Size	Trays: LT - LD (17 - 20 lbs. Bond) Bypass: ST-R - LD (17 - 90 lbs. Index) Bypass: Envelope (with Network Print Kit Only)
Special Media	Text / Text-Photo / Photo
Reduction / Enlargement	25% - 200%
Image Density Control	Standard 250-Sheet Cassette
Paper Supply	Standard 100-Sheet Bypass Optional 2nd 250-Sheet Cassette Optional 550-Sheet Paper Feed Pedestal Optional 550-Sheet 4th Cassette Optional 100-Sheet ADF or RADF (ST-R - LD / 17 - 33.8 lbs. Bond)
Document Feeder	Optional (17 - 20 lbs. Bond)
ADU (Automatic Duplex Unit)	Optional (17 - 20 lbs. Bond)
Dimensions	23.6" x 25.3" x 18.2" (W x D x H)
Weight	Appx. 71lbs.
Toner Type	Cartridge
Toner Yield	24,000 Impressions (100% Recycling Toner System)
Power Supply	115 Volts / 12 Amps

Print Specifications

Standard Printer:	GDI Printing
Max. Print Speed:	19/22/24ppm
Interface:	USB 2.0
Operating System	Windows XP/Vista/7/Server 2003/2008
Duplex Printing	Yes (Manual)

Scan Specifications

Standard Scan	Local TWAIN Scan (Toshiba Viewer)
Resolution	300 x 300 dpi / 600 x 600 dpi
Formats	BMP, TIFF, Multi-TIFF
Max Scan Area	Ledger
Interface:	USB 2.0

Copy Options

Platen Cover	KA-1640PC
Automatic Document Feeder	MR-2020 (100-Sheet)
Paper Feed Unit	MY-1038 (250-Sheet)
64 MB Memory	GC-1240
Harness Kit for Coin Controller	GQ-1130

Copy Options

Platen Cover	KA-1640PC
Automatic Document Feeder	MR-2020 (100-Sheet)
Reverse Automatic Document	MR-3023 (100-Sheet)
ADU	MD-0103 (Stackless)
Paper Feed Unit	MY-1038 (250-Sheet)
Paper Feed Pedestal	KD-1022 (550-Sheet)
Paper Drawer	MY-1028 (550-Sheet)
PFC (Paper Feed Controller)	GH-1060 (Required with KD-1022 and/or MD-0103)
External Keyboard	GJ-1160 (Required with Fax Kit and/or Network Scan Kit)
Harness Kit for Coin Controller	GQ-1130

GA-1192 Network Printing Option

Print Engine Resolution	2400 dpi x 600 dpi (with smoothing)
Print Speed	19/22/24ppm
Memory	128 MB
PDL	PCL6 and PostScript 3 compatible
Interface	10BaseT/100BaseTX/USB 2.0
Protocols	IPX/SPX, TCP/IP, Ether Talk, NetBIOS over TCP/IP
Network Operating System	Windows 2000/XP/Vista/7/Server 2003/2008 Mac OS10.2/10.3/10.4/10.5/10.6

GA-1202 Network Scanning Option

Resolution	150/200/300/400/600 dpi
Scan Speed	20 spm
Scan Mode	B&W, Gray Scale
Scan Memory	128 MB
Scan Type	Scan-to-Email, Scan-to-File (SMB or FTP), Scan-to-FTP, Scan-to-TWAIN
Scan Format	TIFF, PDF

GD-1221NA Facsimile Option

Modem Speed	Super G3 33.6Kbps
Compression Type	MH / MR / MMR / JBIG
Duplex Transmission	Yes (w/RADF)
Memory	5.7 MB (Apprx. 500 Pages)
One Touch Dialing	75
Other Features	Network Fax (Option) and Internet Fax (Option)

Network/Device Management Utility

TopAccess
e-BRIDGE Fleet Management System



Corporate Office 191 McNabb Street, Markham, Ontario L3R 8H2
Tel: (905) 470-3500

Web Site **www.toshiba.ca**

Designs and Specifications subject to change without notice. For best results and reliable performance, always use supplies manufacturer or designated by Toshiba. Not all options and accessories may be available at the time of product launch. Please contact a local Authorized Toshiba Dealership for Availability. Toner yields are estimates based on 6% coverage, letter-size page. Driver and connectivity feature support varies by client/network operating system.